AL-20/AL-24/AL-28/AL-32 **AUTOMATIC LEVELS**



- Magnetically damped compensator designed to ensure high performance and stability
- Compact size with durable all-metal construction
- Large focus and tangent knobs-easy to operate wearing gloves
- Top mounted peep-site for easy target location
- Mirror for easy bubble viewing
- Sealed, weatherproof construction
- Fits standard 5/8" x 11" flat or dome head tripods



PACKAGE INCLUDES

Auto level, plumb bob,
lens cap, Allen wrench,
adjusting pin, instruc-
tion manual and
carrying case.

DESCRIPTION	AL-20	AL-24	AL-28	AL-32
Magnification	20x	24x	28x	32x
Accuracy	±1/16" @ 100'	±1/6" @ 100'	±1/16" @ 100'	±1/16"@ 100'
Approximate Range	175'/50m	250'/75m	300'/90m	350'/100m
Objective Aperture	30mm	30mm	40mm	40mm
Field of view	1' @ 30'	1' @ 30'	1' @ 30'	1' @ 30'
Minimum Focusing Distance	0.5m	0.5m	0.5m	0.5m
Stadia Multiplying Constant	1'=100'	1'=100'	1'=100'	1'=100'
Circular Vial Accuracy	8' /2mm	8' /2mm	8' /2mm	8' /2mm
Setting Accuracy	0.5"	0.5"	0.4"	0.4"
Weight	2.9 lbs./1.3 kg	2.9 lbs./1.3 kg	2.9 lbs./1.3 kg	2.9 lbs./1.3 kg
Base Thread	5/8" or M16	5/8" or M16	5/8" or M16	5/8" or M16
Warranty	1 Year	1 Year	1 Year	1 Year



